### Stock code MEGMEET 002851 WELDING TECHNOLOGY

### **MEGMEET Electrical Co., Ltd** MEGMEET Welding Technology Co., Ltd

Add: 3rd Floor, Block C Unisplendour Information Harbor, Langshan Road, Shenzhen, Guangdong, 518057, China www.megmeet.com (MEGMEET Electrical) www.megmeet-welding.com (MEGMEET Welding Technology) E-mail: welding@megmeet.com Tel: +86-755-8660 0555

MEGMEET Germany GmbH	MEGMEET Türkiye rtibat Büro
Add: Stadtheider Str. 26-28, 33609 Bielefeld, Germany	Add: Merkez Mah. Hasat Sok. No:52/1 Şişli - İstanbul
Tel: +49 521 588 131 40	Tel: +90 538 334 94 88
Email: welding@megmeet.com	Email: welding@megmeet.com
MEGMEET Electrical India Pvt Ltd	MEGMEET (Thailand) Co., Ltd
Add: Plot No. 140, Sector 7, IMT Manesar, Gurugram - 122052, Haryana	Add: 7/375 Moo 6, Tambon M abyangporn, Pluak Daeng, Rayong 21140
Tel: +91 12442 14460	Tel: +66 (0) 33 012 666
Email: welding@megmeet.com	Email: welding@megmeet.com



# **Dex2 Ultra Series**

### Follow us:



Variable Polarity Full Digital IGBT Inverter AC-MIG Welding Machine

MEGMEET's strong technical strength, extensive industry application experience, relentless attention to customer needs, and the spirit of continuous innovation enable us to bring tailor-made products and solutions to help customers achieve greater success.

\*MEGMEET Welding Technology Co., Ltd is continuously striving to develop and innovate for new product. We reserves the right of changing the technical specifications and designs without notices in advance. Copyright 2023 © MEGMEET Welding Technology Co., Ltd





### 2023-07

# Dex2 Ultra 400AC

380 40~70 3PH Hz

Variable Polarity Full Digital IGBT Inverter AC-MIG Welding Machine

CV

110 kHz

### Features

- · Superior welding programs in AC-Pulse MIG, AC short-circuit transition, quick pulse and others, to easily realize high-performance welding of carbon steel, stainless steel, aluminum alloy and other materials;
- Wire feeding speed is faster and deposition rate is increased by more than 20%, under the same current;
- Patented software algorithm enables high-frequency switching of polarity, low heat input, less spatter, and 0.5mm aluminum alloy welding;
- · By adjusting positive and negative polarity ratio of EN/EP, heat input is optimized, and optimal welding of large-gap bridge can be easily achieved;
- · Arc energy is controllable and effectively suppresses the generation of welding fumes. Glossiness of Al-Mg welding is as good as Al-Si welding with more beautiful weld shape;

6

- Inverter frequency up to 110KHz enables higher control precision and more stable arc;
- · Comprehensive communication interfaces are able to communicate with different brands of robots and automation devices;
- Touch sensing function with 80-400 voltage is easier to break down the rust on the surface of workpiece;
- IOT interface is reserved to connect with Megmeet SMARC cloud system;
- · U-disk upgrade function ensures customers to easily obtain Megmeet's most cutting-edge welding technology;
- · Application industries: precision welding in automobiles and parts, two/tricycles, aerospace, military industry, rail vehicles, new energy, etc.





☑ Low spatter arc (LSA) CO₂/MAG ☑ P	ulse MAG/MIG 🛛 🗹 Quick Pulse MAG/MIG			
🗹 Flux Core Carbon Steel/DC 🛛 🗹 A	C short circuit transition CO <sub>2</sub> /MAG/MIG			
🗹 AC Pulse MAG/MIG 🛛 🗹 AC double pulse MAG/MIG 🛛 🗹 Carbon steel				
🗹 Stainless steel 🛛 🗹 Aluminum alloy	U-disk interface SMARC IOT			
Other customization				







Accurate and fast switching of pulse polarity is achieved by Megmeet patented algorithm, which integrates high speed&high efficiency of MIG welding with high quality of TIG welding, greatly optimizes welding production efficiency and welding quality.

### Welding Features:

- High inverter frequency, more stable arc, higher precision;
- With unique negative stability algorithm, AC MIG is as stable as DC weldina:
- Full-process heat input management, precise control of penetration depth, to be easily competent in high-quality welding of 0.5mm ultra-thin plates;
- · By adjusting EN/EP ratio, wire melting speed can be dynamically regulated to realize higher deposition rate and higher welding efficiency;
- · Gap tolerance is high and bridging ability is good, suitable for welding of large-gap lap joints and uneven gaps;
- Welding fume is greatly reduced without black smoke deposition on welding seam, and welding surface is more beautiful.





# AC Short Circuit Transition

High-frequency hardware system working with Megmeet patented algorithm could accurately pre-judge droplet necking. Droplet transition instant polarity is switched to negative arc, and droplet flows freely into fusion pool, which fundamentally eliminates the generation of large-particle spatter and smoke, and ensures high-speed and high-quality welding.

### Welding Features:

- High-speed and stable alternation of polarity, softer arc, 90% less spatter than traditional DC welding;
- · Smooth droplet transition, small fluctuation in fusion pool, and weld shape is more delicate and beautiful;
- · Gap tolerance is high and bridging ability is good, suitable for welding of large gaps and uneven gaps;
- · Ultra-low heat input, to be easily competent in high-quality welding of 0.5mm ultra-thin plates
- · Higher deposition efficiency and faster welding speed, and wire feeding speed is increased by 20% under the same current;
- Arc energy is low and dust amount during welding is small.







- With wider adaptive range of voltage, the same current is able to match lower voltage (10% lower than other welding machines);
- · Lower heat input, higher deposition efficiency, thin-plate welding performance be comparable with tap-type machine.

# Wire Retraction Function in Arc Starting

• When welding machine detects arc starting signal, wire will retract in high speed, which greatly improves the guality and success rate of arc starting, and greatly reduces various arc staring issues.



• Up-down torch is optional to conveniently adjust welding parameters on the torch(current, voltage, etc).



- Built-in high-voltage touch sensing function with adjustable range 80~400V, no need to separately buy high-voltage touch sense device;
- High reliability and effective penetration of oil stains, rust, water stains. etc., fast touch-sense with high precision, and strong adaptability to robots;
- Current-limiting design ensures welding within safe current range. effectively protecting the safety of welders and welding machines;

















• With additional robotic accessories package, manual-type welding power source can be expanded to robotic welding power source to help users save money.



# ✓ High Reliability



Strong environmental adaptability, suitable for working under tough environment;



Stable and reliable: stability is the base of intelligent welding machines!



Consistency: consistent performance by any machine, anytime and anywhere!

# Water Cooler (Optional)

Circulating Water Cooler AnyCool-66			
Water cooler power supply Powered by welding machine			
Rated power	370W		
Rated voltage	380V AC		
Cooling water capacity	6.8L		
Cooling water flow	3.5L/min		
Cooling water maximum lift	20m		
Flow alarm	$\checkmark$		





# Multiple Welding Programs

### AC Pulse

It is mainly used for welding thin plates of aluminum alloy with lower heat input. It can easily realize superior welding of 0.5mm ultra-thin plates and higher deposition efficiency. Welding speed is increased by 20% compared with DC pulse, less dust without black oxides around welding seam.

### AC Short Circuit Transition

It is mainly used to weld thin plates of carbon steel and alloy steel with lower heat input, be competent in welding of 0.5mm ultra-thin plates. Higher deposition efficiency and stronger gap tolerance is ensured.

### QPT(Quick Pulse Technology)

It is mainly suitable for welding of medium&thick plates of carbon steel and stainless steel. It combines advantages of DC and pulse to achieve faster welding speed and less spatter.

# **Product Specification**

Standard Optional

Manual type	Dex2 UI	tra 400AC		
Robotic type*	Dex2 Ultı	ra 400ACR		
Welding Programs	DC	AC		
LSA (Low Spatter Arc by Software)	•	-		
Pulse	•	-		
Quick pulse	•	-		
Flux core carbon steel/DC	•	•		
AC short circuit transition	-	•		
AC pulse	-	•		
AC double pulse	-	•		
Carbon steel	•	•		
Stainless steel	•	•		
Aluminum alloy	•	•		
Function				
U-disk interface	•	•		
SMARC IOT	0	0		
Technical Parameters				
Control Method	Digital IGBT Control			
Input voltage	3-phase AC 380 V (±25%)			
Input frequency	40~70Hz			
Inverter switching frequency	110kHz			
Rated input capacity	16.8KVA/15.5KW			
No-load voltage	77V			
Rated output current	DC 380A/350A	AC 350A/315A		
Rated output voltage	DC 33V/31.5V	AC 31.5V/29.7V		
Duty cycle	60%@380A 100%@350A	60%@350A 100%@315A		
Power factor	0.92			
Efficiency	88%@400A			
Output characteristics	CV			
Wire feeding speed	0.5~28m/min			
Parameter JOB	50			
Operating temperature	-10°C~40°C (welding power source can be started at -39°C)			
Dimension	L*W*H (mm) 647*291*572			
Weight	40KG			
Enclosure rating	IP23 S			
Insulation class	Н			
Cooling mathed	Forced air			





Embedded-Type communication module supports multiple types of communication protocols





# Dex2 Communication Protocols with Robots

	TAST(Thru-	Touch Sensing	Communication Protocols with Robots						
Function	arc Seam Tracking)	80-400V	Analog	DeviceNet	CANopen	MEGMEET CAN	EtherNet/IP	EtherCA	T Profinet
	•	•	0	0	0	0	*	*	*
							Standard	Optional	

## Robotic Wire Feeder Selection

Series	Model Name	Dimensions (L*W*H) mm	Welding Torch Interface	Weight (kg)	
Dex 2	WF1-50ZE	230x170x170	European type	6kg	
	WF1-50ZER	230x170x170	Asian type	6kg	
	WF1-50PW-7	223x152x221	European type	7kg	
	WF1-50PWR-7	223x152x221	Asian type	7kg	

# Manual Wire Feeder Selection

	Enclosed wire feeder		
Model Name	WF2-50P		
Wire feeding drive control mode	Photoelectric encoder feedback /Back electromotive force		
Wire feeder rated current	4.5A		
Wire feeder rated voltage	24V		
Wire feeding speed	0.5~28m/min		
Wire feeding roller diameter	ф0.8~1.6 mm		
Wire spool type	Standard wire spool		
Drive unit	Double drive four rollers		
Wire feeder torch interface	European interface		
Dimension	630*250*400		
Weight	14.5		

